

Glass MULTI-U Agricultural Hydraulic Fluid

Product Data Sheet



Glass MULTI-U Agricultural Hydraulic Fluid is a multi-use, 20W hydraulic fluid manufactured to be used as a general lubricating fluid in agricultural and other general applications requiring SAE 20W hydraulic fluid.

APPLICATIONS:

- **Glass MULTI-U Agricultural Hydraulic Fluid** is formulated for use as a multi-use, general purpose lubricant for use in agricultural applications requiring use of SAE 20W oil.
- Universal, Multi-Use fluid for farming, construction, mining and logging applications.

FEATURES AND BENEFITS:

- Provides a lubricant film for protection against metal to metal contact
- It incorporates a friction modifier to ensure proper noise-free operation
- Provides rust, corrosion and oxidation protection
- Low temperature fluidity provides good response at lower temperatures
- Resists foaming



Typical Characteristics

TEST	Glass MULTI-U
Viscosity, CST @ 40°C	64.7
Viscosity, CST @ 100°C	8.9
Viscosity Index	112
Flash Point, °F (°C), min	439 (226)
API Gravity (60°F)	30.1

The values shown here are representative of current production. Some are controlled by manufacturing specifications, while others are not. All of them may vary within modest ranges.

HAZARDS: "Empty" containers contain residue (liquid and/or vapor) and can be dangerous. Do not pressure, cut weld, braze, solder, drill, grind or expose such containers to heat, flame, sparks or others sources of ignition. "Empty" drums should be completely drained, properly bunged, and promptly returned to a drum reconditioner.

Avoid prolonged contact with skin and frequently change any clothing which may be soiled. In case of contact, wash thoroughly with soap and water for 15 minutes or until the irritation subsides. The formation of mists should be avoided. Do not take internally. If swallowed, do not induce vomiting. Call a physician or Poison Control Center immediately. Keep out of the reach of children.